



TYPE SG & SGS

A sand / salt spreader that can also be used for spreading lime, compost, fertilizer etc.

Bredal A/S has for many years produced lime and fertilizer spreaders for agriculture and its reputation all over the world can be summed up in three key words: Simple, precise & reliable. These 3 words have been the key objectives in developing all Bredal spreaders and this focus has continued in the development of the new SG model.

Simple: The spreader is developed in a way that ensures that daily use, settings and maintenance are made as simple as possible. This ensures accurate application rates and an exact spread pattern with less risk of error.

Precise: Using knowledge built up over the years in spreading a wide range of products including fertilizer, lime, top dressing and compost, Bredal has developed the SG spreader to accurately spread sand and salt for winter use, but also precisely spread fertilizer, lime or sand top dressing etc. out of the winter season.

Reliable: Due to the simple construction and the use of high quality components, Bredal has designed a machine with a long working life. The simple construction also ensures easy maintenance and less risk of down time.



Bredal SG:

- Simple
- Precise
- Reliable
- Professional spreader
- 2 disc spreader
- Precise Spreading over full width
- Positive Metering
- Versatile Spreading
- No agitators
- Easy in operation
- High capacity
- Solid construction

TYPE SG & SGS

SG-Series is available in 3 different versions:

	SG-500	SG-1000	SG-1500	SG-2000
Hopper volume*:	500 ltr	1000 ltr	1500 ltr	2000 ltr
Hopper length*:	1000 mm	1200 mm	1520 mm	1520 mm
Hopper width*:	1400 mm	1750 mm	2000 mm	2000 mm
Loading height*:	1125 mm	1300 mm	1430 mm	1600 mm
Total length*:	1970 mm	2030 mm	2035 mm	2035 mm
Total width*:	1770 mm	1770 mm	2000 mm	2000 mm
Total weight*:	400 kg	420 kg	445 kg	545 kg
Spreading width:	2-10 m	2-10 m	2-10 m	2-10 m

**All info is for standard versions.*

SG- version: Is manually operated using 2 hyd. valves to regulate speed of the floorbelt and spread discs.

SGS- version: Is controlled by the TeeJet500 computer, which allows the spreader to be adjusted from the tractor cab and application rate is forward speed related.

SGS & SG- versions require an oilflow of app. 30 ltr/min

Options

Stainless steel hopper, hopper screen, hopper cover.